

## Dati tecnici

### Orion Evo Multi Split Unità interna



| Modello                             |                   |    | OE09TC1                     | OE12TC1                     | OE18TC1                     | OE24TC1                        |
|-------------------------------------|-------------------|----|-----------------------------|-----------------------------|-----------------------------|--------------------------------|
| Alimentazione elettrica             | F/V/Hz            |    | 220-240~/1/50               | 220-240~/1/50               | 220-240~/1/50               | 220-240~/1/50                  |
| Capacità                            | Raffreddamento    | kW | 2,61(0,94-3,70)             | 3,52(1,00-4,60)             | 5,2 (1,25-5,9)              | 7,0 (1,8-7,8)                  |
|                                     | Riscaldamento     | kW | 3,32(0,94-4,00)             | 3,86(1,00-4,90)             | 5,50(1,25-6,69)             | 7,10(1,85-7,96)                |
| Wi-Fi                               | +/-               |    | +                           | +                           | +                           | +                              |
| <b>Unità interna</b>                |                   |    |                             |                             |                             |                                |
| Dimensioni (LxAxP)                  | mm                |    | 820×306×195                 | 820×306×195                 | 920×306×195                 | 1100×333×222                   |
| Dimensioni dell'imballaggio (LxAxP) | mm                |    | 890×380×265                 | 890×380×265                 | 990×380×265                 | 1165×405×295                   |
| Peso netto                          | kg                |    | 9                           | 9                           | 10                          | 11                             |
| Peso lordo                          | kg                |    | 11                          | 11                          | 13                          | 17                             |
| Portata d'aria                      | m <sup>3</sup> /h |    | 680/650/610/570/540/500/460 | 680/650/610/570/540/500/460 | 900/810/760/700/650/590/530 | 1150/1070/1010/940/890/830/750 |
| Pressione sonora a 1 m di distanza  | dB(A)             |    | 44/41/37/34/29/25/19        | 44/41/37/34/29/25/19        | 47/42/40/38/36/34/32        | 50/44/40/37/34/30/26           |
| Potenza sonora                      | dB(A)             |    | 54/50/47/44/39/35/29        | 54/50/47/44/39/35/29        | 57/52/50/48/46/44/42        | 60/54/50/47/44/40/36           |
| Cavo di comunicazione               | mm <sup>2</sup>   |    | 4x0,75                      | 4x0,75                      | 4x0,75                      | 4x0,75                         |
| Tubo del refrigerante               | inch/mm           |    | 1/4"-3/8"/(Ø6,35-Ø9,52)     | 1/4"-3/8"/(Ø6,35-Ø9,52)     | 1/4"-1/2"/(Ø6,35-Ø12,70)    | 1/4"-1/2"/(Ø6,35-Ø12,70)       |